



civiline

ATEX RIDE-ON BRUSHCUTTERS



Commercial mowing is challenging and competitive with increasing demand for improved productivity and safer operation. The Civiline range of commercial mowers, mulchers and brushcutters meets these challenges with innovative technology.

ATEX RIDE-ON BRUSHCUTTERS

- 1 Kawasaki engine
- 2 **Industry first** front suspension
- 3 Digital hour meter
- 4 Diff-lock for extra traction
- 5 F/R HST control
- 6 Eco throttle for fuel economy
- 7 Blade lever engagement
- 8 Easy stepless cutting height
- 9 Light steering wheel
- 10 Adjustable HST pedals (50mm)
- 11 F/R seat adjustment (up to 60mm)
- 12 Seat safety cutout switch
- 13 Parking brake
- 14 Tight turning circle (2,200mm)
- 15 950mm rear discharge deck



QUICK
WALKTHROUGH
AR950FA



R957 2WD RIDE-ON BRUSHCUTTER

 Kawasaki FS600V
  15°
  10kph
  950mm
  10-80mm
  305kg
  2.2m



SWING OUT SEAT



FRONT SUSPENSION



REAR TOW HITCH



HEAVY DUTY CUTTING


The **Atex R957** is a 2WD ride-on slope brushcutter capable of cutting through grass, shrub, gorse and saplings. It can operate in wet, muddy and hilly conditions. This model now features a front suspension system for improved traction and comfort with a swing out seat for mowing closer to the tree canopy.

AR950FA 4WD RIDE-ON BRUSHCUTTER

 Kawasaki FS691V
  25°
  10kph
  950mm
  35-125mm
  360kg
  2.2m



4WD MOWING



FLAT PLATFORM



ADJUSTABLE HST PEDAL



FRONT SUSPENSION

With 4WD, the **Atex AR950FA** has excellent traction for cutting through grass, shrub, gorse and saplings in wet muddy and hilly conditions. It features an industry-first front suspension system, adjustable seat, flat uncluttered floor and rubber floor mat.

SPECIFICATIONS	R957 (2WD)	AR950FA (4WD)
DRIVE UNIT		
Engine / Power	Kawasaki FS600V	Kawasaki FS691V
Performance (HP)	17.1	24
Displacement (cc)	603	726
Fuel tank capacity	12	14
Fuel	Unleaded	Unleaded
Transmission	HST	HST
Speed (km/h)	0-10	0-10
Drive	2WD	4WD
Difflock	Yes	Yes
Tyre type	3.5-7AGF 16x7-8R	4-7.2F 17x8-8.4R
CUTTING SYSTEM		
Cutting width (cm)	95	95
Cutting height (cm)	1-8	3.5-12.5
PERFORMANCE		
Turning radius (m)	2.2	2.2
Climbing ability	15°	25°
Dimensions (cm)	186 x 106 x 90.5	196.5 x 109 x 95.5
Weight (kg)	305	360
OPTIONS		
Protection frame	Optional	Optional
Bull bar	Optional	Optional